

MASTERTOP[®] TC425

High gloss floor sealer

Description

MASTERTOP TC425 is a gloss floor sealer for use with MASTERTOP Terrazzo flooring systems.

Properties

- Regular cleaning and re-sealing of the floor with MASTERTOP TC425 achieves long finish durability. Old layers of MASTERTOP TC425 can be removed with STRIPPING SOLUTION prior to new layers being installed
- Resistant to alcohol-based hand and floor disinfectants
- Provides a high-gloss, protective layer

Benefits

- The wear-resistant finish protects the floor surface and facilitates daily cleaning
- Responds very well to buffing; most traffic marks are easily removed by buffing
- The high gloss finish can be easily maintained with high speed single disc machines
- Slip-resistant (to ASTM D2047)

Packaging

MASTERTOP TC425 is available in 5 litre packs.

*Technical data

Appearance	Milky white liquid
Relative density	1.04
pH value neat	8.2-8.7

Application procedure

Coverage:

0.015 litres / m² / coat (approx. 3 coats required).

STRIPPING SOLUTION is diluted with 10 parts water, placed on the floor and left to act for 5 minutes. Scrub the floor and then remove all the solution; thoroughly rinse with clean water and allow to dry before applying further coats of MASTERTOP TC425.

Application:

Sparingly pour the MASTERTOP TC425 onto a dry floor and evenly spread it, whilst still wet, polish in overlapping lanes of 1-1.5m. Application should be in one direction only using a figure of 8 movement. Do not allow the material to pond.

Allow to dry completely for around 20-30 minutes (do not force dry) before applying additional coats in an opposite direction to the first coat. Apply two coats to nonporous, smooth floors. Three coats are usually sufficient for porous floors (allowing 20-30 minutes drying time between coats).

NB Do not allow contamination of the sealed surface whilst still wet and do not return unused polish into the container.

Important:

Apply product only on stripped, thoroughly rinsed and completely dry floors. Do not dilute or mix with other substances. Do not store or use at temperatures below 5°C. Do not use on other flooring surfaces without the advice of BASF UAE Technical Services Department. Do not use outdoors or in wet zones.



The Chemical Company

MASTERTOP[®] TC425

Note

Field service, where provided, does not constitute supervisory responsibility. For additional information contact BASF Construction Chemicals UAE LLC.

BASF Construction Chemicals UAE LLC reserves the right to have the true cause of any difficulty determined by accepted test methods.

Quality and care

All products originating from BASF Construction Chemicals UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and OHSAS 18001.

06/2008 BASF_CC-UAE revised 03/2010

* Properties listed are based on laboratory controlled tests.

Whilst any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control.

As all BASF technical datasheets are updated on a regular basis it is the user's responsibility to obtain the most recent issue.

BASF Construction Chemicals UAE LLC

P.O. Box 37127, Dubai, UAE

Tel: +971 4 8090800

Fax: +971 4 8851002

www.basf-cc.ae

