



The Chemical Company

# MASTERFLEX<sup>®</sup> PRIMER NO. 1

**Universal modified silane primer for use with MASTERFLEX<sup>®</sup> 700 and SONOLASTIC series sealants**

## **Description**

A liquid primer used in the preparation of joint surfaces prior to the use of MASTERFLEX<sup>®</sup> 700 & SONOLASTIC range of sealants.

MASTERFLEX<sup>®</sup> PRIMER NO. 1 is used when preparing porous surfaces such as concrete, brickwork, stonework, asbestos and timber and non-porous surfaces such as stainless steel and ceramics.

## **Packaging**

MASTERFLEX<sup>®</sup> PRIMER NO. 1 is available in 750-ml tins.

## **Application temperature**

5°C to 40°C.

## **Coverage**

Theoretical coverage approx. 20m<sup>2</sup> per litre.

## **Watchpoint**

Due to the penetrating and sealing action of MASTERFLEX<sup>®</sup> PRIMER NO. 1, staining may occur on materials such as granite, marble, natural stone and man made composites. If in doubt consult BASF's Technical Services Department.

## **Directions for use**

### **Preparation of surfaces:**

Joint faces to be primed must be completely dry and free from all dirt, dust, cement laitance and other loose and deleterious matter. This is best achieved by grit or sand blasting or thorough wire brushing and then blowing clean with oil free compressed air.

## **Application:**

Pour a small amount of the primer into a clean container ensuring that the main container is tightly resealed. Liberally apply a coat of primer with a soft brush to the required surface. Allow to become tack free before installing MASTERFLEX<sup>®</sup> sealants. If primer is left for more than 3 hours re-priming is necessary. Note: MASTERFLEX<sup>®</sup> PRIMERS are solvent-based.

## **Equipment care**

Clean all brushes immediately with CLEANING SOLVENT.

## **Safety precautions**

Flammable or highly flammable liquids. Do not apply when smoking or near naked flame. Wear protective gloves and goggles. Use in well ventilated areas and avoid breathing of vapour. In the event of narcosis by inhalation of concentrated vapour, remove person to fresh air and call for medical attention. If in contact with eyes, irrigate thoroughly for at least five minutes with clean, cold water and seek medical attention. In the event of a fire, extinguish with carbon dioxide, dry chemical or foam fire extinguisher.

## **Storage**

Store under cover out of direct sunlight and protect from extremes of temperature. In tropical climates the product must be stored in an air conditioned environment.



The Chemical Company

# MASTERFLEX<sup>®</sup> PRIMER NO. 1

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult BASF's Technical Services Department.

## Note

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local BASF representative.

BASF reserves the right to have the true cause of any difficulty determined by accepted test methods.

## Quality and care

All products originating from BASF's Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and OHSAS 18001.

04/2003 BASF\_CC-UAE revised 05/2006

---

Whilst any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control.

**As all BASF technical datasheets are updated on a regular basis it is the user's responsibility to obtain the most recent issue.**

---

**BASF Construction Chemicals UAE LLC**

P.O. Box 37127, Dubai, UAE

Tel: +971 4 8090800

Fax: +971 4 8851002

www.basf-cc.ae

