

CLEANING SOLVENT NO. 2

Description

A volatile blend of hydrocarbon solvents, specifically designed for cleaning equipment when using BASF epoxies, polyurethanes and polysulphides.

Typical properties

Properties listed are only for guidance and are not a guarantee of performance

Flashpoint:	27°C
Specific gravity:	0.860
Colour:	clear / yellow liquid

Note

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local BASF representative.

BASF reserves the right to have the true cause of any difficulty determined by accepted test methods.

08/95 BASF-CC-UAE revised 05/2006

Shelf life

Indefinite in tightly sealed original containers.

Storage

CLEANING SOLVENT NO. 2 contains a flammable solvent all normal precautions should be taken in both storage and use. Store in closed containers in cool, dry conditions away from sources of ignition.

Safety precautions

Wear goggles, gloves and face mask during use. As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Reseal containers after use. Use in well ventilated areas and avoid inhalation.

Whilst any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control.

As all BASF technical datasheets are updated on a regular basis it is the user's responsibility to obtain the most recent issue.

BASF Construction Chemicals UAE LLC

P.O. Box 37127, Dubai, UAE

Tel: +971 4 8090800

www.basf-cc.ae

Fax: +971 4 8851002

e-mail: marketingcc.mideast@basf.com



Certificate No.
963680



Certificate No.
945787



Certificate No.
772556