

Tinted Primer

Description

100% acrylic-based primer

Substrates, for further information on substrate preparation.

Primary uses

- TINTED PRIMER helps alleviate shadowing and enhances performance of the Senergy Wall Systems. For optimum results, TINTED PRIMER should closely match the colour of the selected Senergy Finish.
- TINTED PRIMER is also used when preparing substrates such as poured concrete, unit masonry, conventional stucco (brown coat), veneer plaster or gypsum board (interior only) prior to application of Senergy Finish Coat. See Senergy Technical Bulletin, Application of Finishes over Approved

Packaging

24.9kg per 19 litre unit

Colours

Available in 126 standard colours and a wide variety of custom colours.

Coverage

Approximate coverage rate:

69.6–116.1m² per unit. Coverage will vary greatly depending on porosity and condition of surface.

Features	Benefits
Reduces suction by cement base coats and cementitious substrates	Improves workability of finish coat application
Tinted to finish colour	Creates better final appearance, alleviates shadowing of light-coloured, rilled finishes
Improves water resistance of the wall	Reduces chances of efflorescence in stucco and other cementitious substrates

Tinted Primer

Mixing

- Thoroughly mix the factory-prepared TINTED PRIMER with a paddle and drill to a uniform consistency.
- A small amount of clean, potable water may be added to adjust workability.
- Additives are not permitted.
- Close container when not in use.
- Clean tools with soap and water immediately

Application

- Substrate shall be dry, clean, sound and free of releasing agents, paint or other residue or coatings. Verify substrate is flat, free of fins or any irregularities greater than 6.4mm in 3m.
- Apply TINTED PRIMER to substrate with a sprayer, 10mm nap roller or good quality latex paint brush at a rate of approximately 3.6–6.1m² per litre.
- TINTED PRIMER shall be dry to the touch before proceeding to the Senergy Finish Coat application.

Limitations

- Protect Senergy materials during transportation and installation to avoid physical damage.
- Store Senergy materials in a cool, dry place protected from freezing conditions. Store at no less than 4°C. Protect from extreme heat and direct sunlight. Shelf life is 6 months when unopened and stored as directed.

- Do not apply Senergy materials in ambient temperatures below 4°C. Provide supplementary heat during installation and drying period (at least 24 hours after installation and until dry) when temperatures less than 4°C prevail.
- Do not apply Senergy materials to frozen surfaces.

Technical Information

Consult the BASF Construction Chemicals Technical Services Department for specific recommendations concerning all other applications. Consult the Senergy website, www.senergy.cc, for additional information about products and systems and for updated literature.

Tinted Primer

Health and Safety

Caution

Contains acrylic copolymer, titanium dioxide, inorganic filler, propylene glycol.

Precautions

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Keep container closed when not in use. DO NOT take internally. Use only with adequate ventilation. Use impervious gloves, eye protection and if the TLV is exceeded or used in a poorly ventilated area, use NIOSH/MSHA approved respiratory protection in accordance with applicable Federal, state and local regulations.

Risk

May cause skin, eye or respiratory irritation. Ingestion may cause irritation.

First Aid

- For eye contact, flush thoroughly with water for at least 15 minutes.
- For skin contact, wash affected areas with plenty of water, and soap if available, for several minutes. SEEK IMMEDIATE MEDICAL ATTENTION if irritation develops and persists. Remove and wash contaminated clothing.
- If inhalation causes physical discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs or if swallowed, SEEK IMMEDIATE MEDICAL ATTENTION.

Read Material Safety Data Sheet before using this product.

10/2007 BASF_CC-UAE revised 03/2010

Note:

BASF Wall Systems is an operating unit of BASF Construction Chemicals, LLC. (herein after referred to as "BASF Wall Systems")

Residential Policy

On one and two-family residential framed construction, BASF Wall Systems requires that the wall system selected be one that includes provisions for moisture drainage. The choices include Senturion® line of water managed EIFS, commercial Senerflex® Wall Systems integrating moisture management features, Senergy Stucco Wall System, and Senergy Cement- Board Stucco™ Systems. Senergy Exterior Surfacing Systems for insulating concrete forms are also acceptable. There are no exceptions to this policy. Under no circumstances will BASF Wall Systems warrant the use of any other system on this type of construction without expressed written authorization from BASF Wall Systems [Residential construction using EIFS on masonry (CMU) or poured concrete does not require the additional water management provisions described above.] See the Senergy Residential Policy Bulletin for a more detailed discussion of this topic. Consult BASF Wall Systems Technical Services Department for specific recommendations concerning all other applications. Consult the Senergy web-site, www.senergy.cc for additional information about products and systems and for updated literature.

Disclaimer

This information and all further technical advice are based on BASF Wall Systems present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, BASF Wall Systems disclaims any and all CONDITIONS AND WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. BASF WALL SYSTEMS SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. BASF Wall Systems reserves the right to make any changes according to technological progress or further developments. It is the customers responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used.

Whilst any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control.

As all BASF technical datasheets are updated on a regular basis it is the user's responsibility to obtain the most recent issue.